

## TECHNICAL DAT SHEET

### ENDURA Penetrating Grease

**DESCRIPTION:** Endura is a high strength lubricant with exceptional adhesive strength. It sprays as a liquid, penetrates tight areas and sets up as a long lasting grease. PTFE is added, giving Endura greater lubricity and heat resistance. This exclusive formula assures that the product will penetrate and stay where it is sprayed, resist throw off, squeeze out, high pressure and water. Endura provides protection against rust, corrosion acids, alkalis and has a temperature range of -30°F to over 600°F. Endura is also salt resistant.

**USES:** \*Open Gears \*Door Hinges \*Chains and Sprockets \*Marine applications \*Rubbish Companies \*Fleet Truck \*Lawn Equipment \*Farm Equipment

**DIRECTIONS:** 1. Spray area to be treated long enough to saturate.  
2. Allow to penetrate.

**PACKAGING:** 16 oz aerosol                      12/case

**STORAGE:** Store below 120°F.

**SPECIFICATIONS:**

Color	clear	Odor	solvent
Specific Gravity	0.7	Density	4.0
Flash Point	-40°F	Freeze Stable	yes
Effect on Paint	none		

**STORAGE:** Store below 120°F.

**PRODUCT #:** C1630

**DATE REVISED:** 10/07/98