

TECHNICAL DATA SHEET

Z-3 Under Coat

DESCRIPTION: Z-3 is a heavy duty, non-paintable undercoat and sound deadner. This is a low cost way to re-coat fender wells and under carriage. Tough film will not pinhole, sag or drip in normal application. Z-3 exceeds US Government specifications for undercoating (TT-C-502A). Avoid application of undercoating closer than 12 to 14 inches from entire exhaust system. Z-3 is superior salt corrosion protection.

USES: *Rust Prevention *Tree Wound Dressing *Auto Undercoat *Trailers
*Trailer Undercoat *Wood Fence Post Preserver *Eaves, Troughs & Flashing Sealer

DIRECTIONS:

1. Shake product well before and during use.
2. Spray, holding can 8 to 10 inches from surface, using smooth and easy movement.
3. Coating will dry in about 2 hours.
4. clean valve by inverting can and spraying until only pressure escapes.

PACKAGING: 24 oz aerosol 12/case

STORAGE: Store below 120°F.

SPECIFICATIONS:

Color	black
Specific Gravity	0.9
Flash Point	-40°F
Cleaning	N/A
Odor	solvent
Density	4.0
Freeze Stable	yes

PRODUCT #: C2401

DATE REVISED: 09/30/98