

# PRODUCT INFORMATION



ENVIRONMENTALLY RESPONSIBLE  
SILICONE  
SPRAY LUBRICANT

CODE: AM9-14

PAGE: 1 of 1

DATE: March, 97

**FUNCTION & APPLICATION:** Stops squeaking and sticking, prevents rust and corrosion, lubricates doors, locks, drawers, and windows. It is also useful for other home applications as well as for automotive, shop, and industrial use, and for sports and athletic equipment.

**NOTE:** Not suitable for equipment or surfaces which do not permit quick evaporation to the open air. Some surfaces, such as treadmills, require faster evaporation than this product affords. Not recommended for mold release applications.

**ENVIRONMENTALLY RESPONSIBLE:** This product has been formulated to reduce or eliminate adverse environmental characteristics. It is Non-Corrosive, and contains No Ozone Depleters and No Chlorinated Solvents.

**USE DIRECTIONS:** Shake container well before using. Spray surfaces lightly. Take care to avoid spraying on floors or stairways. Work lubricant in by moving parts and surfaces back and forth.

**PRECAUTIONS:** Contains Petroleum Distillate (CAS# 142-82-5), Propane Propellant (CAS# 74-98-6), and Dimethyl polysiloxane (CAS# 63148-98-6). Contents under pressure. Inhaling concentrated vapors, intentionally or otherwise, can be harmful or fatal. **FIRST AID:** In case of eye contact, flush thoroughly with water for 15 minutes while lifting eyelids. Consult a physician if adverse effects persist. If swallowed, DO NOT INDUCE VOMITING! Get medical attention immediately! If inhaled, move to fresh air immediately. If breathing is difficult, administer oxygen; if breathing has stopped, apply artificial respiration. Keep warm and summon medical assistance. In case of skin contact, wash thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

**STORAGE & HANDLING:** Store in a cool, dry, well ventilated area. Do not puncture or incinerate container. Do not expose to heat, sparks, open flames or temperatures above 120 F. Exposure to high temperatures may cause bursting. Do not place on radiator, stove or in direct sunlight. Keep from contact with electrical connections such as battery terminals. Keep away from children and animals.

**DISPOSAL:** Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

**CONTAINER DESCRIPTION:** This product is packed in 13 ounce aerosol container.

## Radiator Specialty Company

P.O. BOX 34689 / CHARLOTTE, N.C. 28234 / TELEPHONE 704-377-6555

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.

© 1997 Radiator Specialty Company

