

PRODUCT INFORMATION



10-MINUTE FLUSH

CODE	C14
PAGE	1 of 1
DATE	March 2000

FUNCTION AND APPLICATION: Flushes rust, scale and deposits from the cooling system when changing coolant or as a periodic cleaner.

OUTSTANDING PROPERTIES: Cleans grease, oil, scum and deposits from the cooling system in 10 minutes. Does not require a neutralizer. Contains no acids.

USE DIRECTIONS: Let engine idle for 5 minutes. Drain cooling system. **NOTE:** Used anti-freeze/coolant and radiator fluids may be considered hazardous in some areas. Dispose of in sanitary sewer system where permitted. Never pour onto ground or into storm or septic sewer systems. (See DISPOSAL, below) Pour entire contents of container into radiator and refill with water. Run engine 10 minutes and drain system. Flush until water is clean. Refill cooling system. Use caution when removing radiator cap while system is hot. Run engine while filling system to prevent damage.

PRODUCT LIMITATIONS: A mild cleaner. Will not flush out severe accumulations of deposits and rust. Adequate for most applications. For severely clogged systems, use SOLDER SEAL® GUNK® Super Heavy Duty Radiator Cleaner (C22-32) or consult a professional radiator repair shop.

PRECAUTIONS: Contains 2-Butoxy-1-Ethanol (CAS# 111-76-2). May cause eye burns. Prolonged skin exposure may cause burns or organic damage. Harmful or fatal if swallowed. KEEP AWAY FROM CHILDREN. **FIRST AID:** If eye contacted, flush with water for at least 15 minutes. Call a physician. If skin is contacted, wash thoroughly with soap and water. If irritation persists, consult a physician. If swallowed, Give two glasses of water. INDUCE vomiting!. Consult a physical immediately for medical attention.

STORAGE & HANDLING: Store away from oxidizing agents and strong acids.

DISPOSAL: Use and dispose of product, container, residue and used Anti-freeze/coolant and Radiator Fluids in accordance with all local, state and federal laws and regulations. Where permitted, dispose of in sanitary sewer systems. Never pour onto ground or into storm sewer systems.

CONTAINER DESCRIPTION: Packed 11 fluid ounces in a plastic bottle.

Radiator Specialty Company

P.O. BOX 34689 / CHARLOTTE, N.C. 28234 / TELEPHONE 704-377-6555

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.