

PRODUCT INFORMATION



HEAVY-DUTY
BLOCK SEAL

CODE: C6-16

PAGE: 1 of 1

DATE: March, 97

FUNCTION AND APPLICATION: Repairs cracked engine blocks, cylinder heads, valve parts, water jackets. For all water cooled engines.

OUTSTANDING PROPERTIES: A specially compounded engine block and cylinder head repair designed to form a rugged temperature resistant bond.

USE DIRECTIONS: NOTE: Be sure cooling system is clean. Remove all rust, scale and sludge. Use SOLDER SEAL HEAVY-DUTY RADIATOR CLEANER, for flushing, neutralizing and reflushing per product instructions. If anti-freeze is in system, drain and flush before using. Clean anti-freeze may be replaced after repair is completed as follows; SHAKE WELL BEFORE USING. Fill radiator allowing room for expansion and addition of LIQUID BLOCK SEAL. Radiator hose or thermostat need not be removed. Pour in contents and run engine until temperature is well above normal (180-200F). Continue engine operation at high temperature (DO NOT BOIL) for 5 to 10 minutes or until visible leak stops. Drain entire system and let repair set for 1/2 hour before refilling. Flush with clear water then refill system. When used according to directions, LIQUID BLOCK SEAL cannot impair circulation.

PRODUCT LIMITATIONS: In severe cases repairs may be only temporary. In this situation replacement of the block may be necessary.

PRECAUTIONS: Contains Sodium Silicate (CAS# 1344-09-8). Eye and skin irritant. Harmful if swallowed. Avoid contact with skin, eyes or clothing. Do not take internally. **FIRST AID:** In case of contact, immediately flush skin or eyes with plenty of water for at least 15 minutes and get medical attention. If swallowed, DO NOT induce vomiting! Drink water followed by citrus fruit juice. Call a physician immediately!

STORAGE & HANDLING: Store in a cool, dry place below 120°F. away from acids, ignition sources and oxidizing agents. Keep from freezing. KEEP AWAY FROM CHILDREN.

DISPOSAL: Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

CONTAINER DESCRIPTION: 15 fl. oz. fill plastic jug.

Radiator Specialty Company

P.O. BOX 34689 / CHARLOTTE, N.C. 28234 / TELEPHONE 704-377-6555

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.