

PRODUCT INFORMATION



LIQUID WRENCH®
SUPER PENETRANT
AEROSOL

CODE: L1-06, 12

PAGE: 1 of 1

DATE: April, 97

FUNCTION AND APPLICATION: A point-of-use penetrant for use by mechanics and do-it-yourselfers for disassembly of corroded pipe joints, rusted bolts and machinery, painted or gummed up metal mechanisms. Also used to clean typewriters, guns, and sports equipment.

OUTSTANDING PROPERTIES: A versatile, multi-use penetrant.

USE DIRECTIONS: Spray or squirt product on frozen joint or part. Tap the joint to set up vibrations. If part is stubborn, repeat application and allow to soak into joint for a few minutes.

PRODUCT LIMITATIONS: Does not furnish long-term lubrication or oil film protection.

PRECAUTIONS: Contains Aliphatic Petroleum Distillate (CAS# 8008-20-6), Petroleum Mineral Oil (CAS# 64742-06-9), & Carbon Dioxide (CAS# 124-38-9) Flammable. Harmful or Fatal if Swallowed. Eye and Skin Irritant. Vapor Harmful. Contents under pressure. **FIRST AID:** If swallowed DO NOT INDUCE VOMITING. Get medical attention immediately. If eye contacted, flush with water for at least 15 minutes. Call a physician. If skin is contacted, wash thoroughly with soap and water. If inhaled, move to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, apply artificial respiration. Call a physician immediately.

STORAGE & HANDLING: Store in a dry, well ventilated area below 120°F/49°C. Do not puncture, crush or incinerate (burn) can. Wash thoroughly after handling. **FIRE:** Use only in a well ventilated area away from heat, sparks and flame. Pilot lights of furnaces or hot water tanks can ignite vapors. Do not use in confined spaces, enclosed garages, basements or low lying areas where vapors can collect. Do not place can on hot surfaces or in direct sunlight which could cause can to burst violently. Keep can from contact with electrical current or connections such as battery terminals because burn through may occur. Explosion or flash fire from vapors may cause serious injury or death.

CONTACT: Avoid contact with eyes, skin or clothing. Remove contaminated clothing and wash before reuse. Remove contact lenses before use. Wear chemical goggles and solvent-proof gloves and apron. **BREATHING:** Do not breathe vapors, gas or mist. Use only in well ventilated area. Operate doors and windows to prevent build up. See M. S. S. for more information.

DISPOSAL: Dispose of container, residue and excess product in accordance with all federal, state and local laws and regulations. Emptied containers contain product residue, so follow all warnings even after container is emptied.

CONTAINER DESCRIPTION: 11 and 6 oz wt. aerosol containers.

Radiator Specialty Company

P.O. BOX 34689 / CHARLOTTE, N.C. 28234 / TELEPHONE 704-377-6555

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.

