

PRODUCT INFORMATION



WIRE DRYER

CODE: M13-06

PAGE: 1 of 1

DATE: March, 97

FUNCTION AND APPLICATION: Dries wet ignition systems. Prevents reoccurrence of wetting. Leaves distributor, wires and coil weatherproofed.

OUTSTANDING PROPERTIES: Protection lasts for several weeks per application. Use of product is easy and fast without special tools or skill.

USE DIRECTIONS: Open hood of car. Spray electrical system, including distributor, wires, coil, battery and cables and all electrical wires and plugs. In severe humidity or dampness, spray inside of distributor cap, but allow some time for drying before replacing distributor cap. Allow all parts to dry sufficiently before starting engine.

PRECAUTIONS: Contains Aliphatic Petroleum Distillate (CAS# 8052-41-3), 2-Butoxy-1-Ethanol (CAS# 111-76-2), Napthenic Petroleum Oil Mixture (CAS# 64742-53-6/64742-52-5), Tertiary Amine (CAS# 95-38-5), and Carbon Dioxide Propellant (CAS# 124-38-9). Combustible. Harmful or Fatal if Swallowed. Eye and Skin Irritant. Vapor Harmful. Contents under pressure. **FIRST AID:** If swallowed DO NOT INDUCE VOMITING. Get medical attention immediately. If eye contacted, flush with water for at least 15 minutes. Call a physician. If skin is contacted, wash thoroughly with soap and water. If inhaled, move to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, apply artificial respiration. Call a physician immediately. See M. S. D. S. for more information.

STORAGE & HANDLING: Store in a dry, well ventilated area below 120°F/49°C. Do not puncture, crush or incinerate (burn) can. **FIRE:** Use only in a well ventilated area away from heat, sparks and flame. Pilot lights of furnaces or hot water tanks can ignite vapors. Do not use in confined spaces, enclosed garages, basements or low lying areas where vapors can collect. Do not place can on hot surfaces or in direct sunlight which could cause can to burst violently. Keep can from contact with electrical current or connections such as battery terminals because burn through may occur. Explosion or flash fire from vapors may cause serious injury or death. **CONTACT:** Avoid contact with eyes, skin or clothing. Remove contaminated clothing and wash before reuse. Remove contact lenses before use. Wear chemical goggles and solvent-proof gloves and apron. **BREATHING:** Do not breathe vapors, gas or mist. Use only in well ventilated area. Open doors and windows to prevent build up. See M. S. D. S. for more information. **KEEP AWAY FROM CHILDREN.**

DISPOSAL: Dispose of container, residue and excess product in accordance with all federal, state and local laws and regulations. Emptied containers contain product residue, so follow all warnings even after container is emptied.

CONTAINER DESCRIPTION: Packaged in 6 oz (170g) net wt aerosol can.

Radiator Specialty Company

P.O. BOX 34689 / CHARLOTTE, N.C. 28234 / TELEPHONE 704-377-6555

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.