

PRODUCT INFORMATION



DIESEL FUEL
ANTI-GEL
COLD FLOW IMPROVER

CODE
M22-16,-40,-49
PAGE
1 of 1
DATE
March, 97

FUNCTION AND APPLICATION: Retards waxing and gelling during cold weather. Stops filter icing. Reduces pour point of diesel fuel.

OUTSTANDING PROPERTIES: Lets fuel flow freely at low temperatures. Cuts costly downtime due to clogged filters.

USE DIRECTIONS: To retard waxing and gelling, add 1 pint (16-oz.) ANTI-GEL to each 125 gallons of fuel when outside temperature drops to approximately 20°F (7°C). Add 3 or 4 ounces per 25 gallons capacity for passenger cars. Using excess amounts of ANTI-GEL will not be harmful.

PRECAUTIONS: Contains Aliphatic Petroleum Distillate (CAS# 8008-20-6), Aromatic Petroleum Distillate (CAS# 64742-95-6) and Aromatic Hydrocarbon Solvent Mixture. Combustible. Harmful or fatal if swallowed. Vapor harmful. Eye and skin irritant. **FIRST AID:** If swallowed, DO NOT INDUCE VOMITING! DO NOT ADMINISTER ADRENALINE OR EPINEPHRINE! Get medical attention immediately! If inhaled, move to fresh air immediately. If breathing is difficult, administer oxygen; if breathing has stopped, apply artificial respiration. Keep warm and summon medical assistance. For eye contact, flush thoroughly with water for 15 minutes while lifting eyelids. Consult a physician if adverse effects persist. If skin contacted, wash thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

STORAGE & HANDLING: Store in a cool place below 120°F. away from acids, ignition sources and oxidizing agents. Use with adequate ventilation. Avoid breathing vapors. Wearing contact lenses while working with this product is inadvisable. KEEP AWAY FROM CHILDREN.

DISPOSAL: Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

CONTAINER DESCRIPTION: 16 fluid ounce metal can, or plastic bottle.

Radiator Specialty Company

P.O. BOX 34689 / CHARLOTTE, N.C. 28234 / TELEPHONE 704-377-6555

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.