

# PRODUCT INFORMATION



**AIR BRAKE SYSTEM  
ANTI-FREEZE  
&  
RUST GUARD**

**CODE:** M28-32, -34

**PAGE:** 1 of 1

**DATE:** March, 97

**FUNCTION AND APPLICATION:** An anti-freeze designed to prevent freezing of water, and corrosion to metals in lines of heavy duty air brake systems.

**OUTSTANDING PROPERTIES:** AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD is identified by its blue color. Contains effective corrosion inhibitors and conditioners to protect metals in air brake systems. NOTE: Contains an effective aversive agent(d-Denatonium benzoate (CAS# 3734-33-6), the most bitter substance known) and child resistant closures to prevent children from ingesting the product. Only prime methanol is used to guarantee quality and avoids corrosive by-products found in some recycled solvents used by competitive brands. Strict quality control in manufacturing, blending and filling, assures the finest product and performance. Over twenty years of on-the-road use history backs up the effectiveness and acceptance of AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD.

**USE DIRECTIONS:** Pour AIR BRAKE ANTI-FREEZE into alcohol evaporator until container is two thirds full. Bubbles should pass through ANTI-FREEZE while compressor is operating. Make sure all connections are tight and in good condition.

**PRODUCT LIMITATIONS:** Avoid contact with painted surfaces.

**PRECAUTIONS:** DANGER. POISON. Contains METHANOL (CAS# 67-56-1). Cannot be made nonpoisonous. **Harmful or fatal if swallowed!** Eye and skin irritant. Vapors harmful. **FIRST AID:** In case of ingestion drink plenty of water, milk, or 4% sodium bicarbonate. Induce vomiting. Seek medical attention immediately. In case of eye contact, flush thoroughly with water for 15 minutes while lifting eyelids. Consult a physician if adverse effects persist. For skin contact, wash thoroughly with soap and water. Remove contaminated clothing and launder before re-use. If inhaled, Move to fresh air immediately. If breathing is difficult, administer oxygen; if breathing has stopped, apply artificial respiration. Keep warm and summon medical assistance.

**STORAGE & HANDLING:** Store in cool place below 120 F away from oxidizing agents, acids, ignition sources and open flame. Wearing contact lenses while working with this product is inadvisable. **KEEP AWAY FROM CHILDREN AND ANIMALS!**

**DISPOSAL:** Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

**CONTAINER DESCRIPTION:** Available in 32 oz., 1-gallon, and 54-gallon sizes.

## Radiator Specialty Company

P.O. BOX 34689 / CHARLOTTE, N.C. 28234 / TELEPHONE 704-377-6555

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.