

PRODUCT INFORMATION



STARTING FLUIDS
THRUST®
INSTANT®
LIQUID FIRE

CODE
M35-15, M38-15, M39-11
PAGE
1 of 1
DATE
March, 97

FUNCTION AND APPLICATION: To promote quick starting of gasoline and diesel engines under extreme cold conditions.

OUTSTANDING PROPERTIES: Produce quick, smooth starting of gasoline and diesel engines under extreme cold conditions down to -65°F. Saves battery and ignition during cold weather. Contains upper cylinder lubricant and corrosion inhibitors.

USE DIRECTIONS: Spray fluid directly into air cleaner of air intake before starting engine. Avoid spraying for over 5 seconds per attempt. If engine still refuses to start repeat procedure for up to 3 times. If engine still does not start, ignition repairs may be indicated.

ALWAYS AVOID SPRAYING WHILE IGNITION IS ON TO AVOID POSSIBILITY OF EXPLOSION OR FIRE.

PRODUCT LIMITATIONS: Avoid spraying while turning engine simultaneously. Avoid overuse of product when engine fails to start with recommended procedure. Engine damage or personal injury may result. Avoid flooding engine before using. Do not use with engines which use glow plugs (especially diesel passenger autos).

PRECAUTIONS: Contains Diethyl Ether (CAS# 60-29-7), Aliphatic Petroleum Distillate (CAS# 142-82-5), Petroleum Dewaxed Heavy Paraffinic Solvent (CAS# 64742-65-0), and Carbon Dioxide Propellant (CAS# 124-38-9). Extremely flammable. Can be explosive when subjected to

heat, sparks or open flame. Vapors extremely harmful. Contents under pressure. Eye and skin irritant. Harmful or fatal if swallowed. **FIRST AID:** In case of inhalation, move to fresh air immediately. If breathing is difficult, administer oxygen; if breathing has stopped, apply artificial respiration. Keep warm and summon medical assistance. For eye contact, flush thoroughly with water for 15 minutes while lifting eyelids. Consult a physician if adverse effects persist. For skin contact, wash thoroughly with soap and water. Remove contaminated clothing and laundry before re-use. If swallowed, DO NOT INDUCE VOMITING! DO NOT ADMINISTER ADRENALINE OR EPINEPHRINE! Get medical attention immediately!

STORAGE & HANDLING: Store in a cool, dry, well ventilated area. Do not puncture or incinerate container. Do not expose to heat, sparks, open flames or temperatures above 120 F. Exposure to high temperatures may cause bursting. Do not place on radiator, stove or in direct sunlight. Keep from contact with electrical connections such as battery terminals. Use with adequate ventilation. Avoid using in low lying or confined areas. Wearing contact lenses while working with this product is inadvisable. Keep away from children.

DISPOSAL: Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

CONTAINER DESCRIPTION: 15 weight ounce and 11 weight ounce aerosols.

SPECIAL NOTATIONS: See above caution and warning statements.

Radiator Specialty Company

P.O. BOX 34689 / CHARLOTTE, N.C. 28234 / TELEPHONE 704-377-6555

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.