

# PRODUCT INFORMATION



**NU-POWER®  
ENGINE TREATMENT  
WITH PTFE\***

**CODE: M62-32**

**PAGE: 1 of 1**

**DATE: February, 98**

**FUNCTION AND APPLICATION:** **NU-POWER® Engine Treatment** with PTFE\* is scientifically formulated to blend with both petroleum and compatible synthetic oils. This unique formulation provides superior lubrication in all gasoline and diesel engines (old and new).

**OUTSTANDING PROPERTIES:** Contains PTFE\* Laboratory tested by ATSM D4172, 2670, 3233, to show improved wear resistance, friction reduction at extreme pressure loads. **NU-POWER®** is formulated from the highest quality ingredients available and special blending, bonding and suspension agents.

**USE DIRECTIONS:** 1. Drain oil and change oil filter. 2. Refill with high quality motor oil only, minus the amount of **NU-POWER® Engine Treatment** to be added. Do not add other oil additive product. 3. Shake bottle well and pour in engine crankcase. 4. Immediately drive the vehicle to allow **NU-POWER® Engine Treatment** to reach internal engine parts. 5. Drive vehicle and enjoy the benefits of **NU-POWER® Engine Treatment**. Change oil every 3500 miles or manufacturer's recommended oil change interval (see owner's manual).

**NOTE:** Use after factory-recommended break-in period as specified in owner's manual. Failure to follow the above recommended procedures may result in poor or ineffective treatment.

**USE RATIO:** Add 20% by volume of **NU-POWER® Engine Treatment** to oil. A five quart capacity engine requires one quart of **NU-POWER®**. Use proportional to engine oil capacity.

**PRECAUTIONS:** Contains Solvent Refined Paraffinic Petroleum Oil (CAS# 64741-88-4/64742-65-0), Hydrofinished Solvent Refined Paraffinic Petroleum Oil (CAS# 64742-54-7) and Proprietary Additives (CAS# Mixture). May be harmful if swallowed. Prolonged skin exposure may cause irritation. **FIRST AID:** If swallowed, DO NOT INDUCE VOMITING. Consult a physician immediately. If eye contacted, flush with water for at least 5 minutes. If skin is contacted, wash thoroughly with soap and water.

**STORAGE AND HANDLING:** Store in a cool, dry area. Keep away from children. Wearing contact lenses while working with this product is inadvisable.

**DISPOSAL:** Recycle used motor oil. Dispose of container, residue and excess product in accordance with all federal, state and local laws and regulations.

**CONTAINER DESCRIPTION:** This product is available in 1 quart size plastic bottle.

- Polytetrafluoroethylene

## **Radiator Specialty Company**

P.O. BOX 34689 / CHARLOTTE, N.C. 28234 / TELEPHONE 704-377-6555

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.