

PRODUCT INFORMATION



MOTOR FLUSH

Code: MF-2ES

Page: 1 of 1

Date: Sept. 1998

FUNCTION AND APPLICATION: A blend of sludge dissolving solvents which can be added to an engine a few minutes before an oil change to flush out deposits and free valves and rings.

OUTSTANDING PROPERTIES: Frees up sludge associated with slow city driving. Can be easily used by car owners or professional technicians just before oil changes,

USE DIRECTIONS: 1. Check that engine oil is at a safe operating level. 2. Add MF to cold engine before changing oil and filter. Idle-engine at normal speed for 5 minutes. GUNK® Motor Flush will circulate throughout the entire lubricating system of your engine removing sludge, gums and varnishes from engine and oil pan. It also frees sticking valves and rings. DO NOT DRIVE CAR. 3. Drain oil and remove oil filter. 4. Replace filter and drain plug and refill engine with new oil. NOTE: On engines with high mileage or excessive deposits remove and clean the oil pan. IMPORTANT: Use entire contents of container after opening. Do not store partially used container.

PRECAUTIONS: Contains petroleum distillate mixture. Combustible. Eye and skin irritant. Vapor harmful. Harmful or fatal if swallowed. **FIRST AID:** In case of eye contact, flush thoroughly with water for 15 minutes while lifting eyelids. Consult a physician if adverse effects persist. For skin contact, wash thoroughly with soap and water. Remove contaminated clothing and launder before re-use. If inhaled, move to fresh air immediately. If breathing is difficult, administer oxygen; if breathing has stopped, apply artificial respiration. Keep warm and summon medical assistance. If swallowed, DO NOT INDUCE VOMITING! DO NOT ADMINISTER ADRENALINE OR EPINEPHRINE! Get medical attention immediately!

STORAGE & HANDLING: Store in a cool place below 120°F. away from acids, ignition sources and oxidizing agents. Keep away from heat and flame. Product spilled on hot surfaces may ignite. Keep away from children.

DISPOSAL: Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

CONTAINER DESCRIPTION : Packaged in 30 fluid oz metal can (MF-2) or 15 (MF-15) and 32 fluid oz (MF-3) plastic bottle.

Radiator Specialty Company

P.O. BOX 34689 / CHARLOTTE, N.C. 28234 / TELEPHONE 704-377-6555

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.

