

# PRODUCT INFORMATION



## TITE-SEAL® UNDERCOATING

**CODE:** T16-

**PAGE:** 1 of 1

**DATE:** April, 97

**FUNCTION AND APPLICATION:** An aerosol undercoating designed to protect car body from rust and corrosion. Useful after do-it-yourself repairs and replacement of parts. Protects against moisture, dirt, corrosive road salt and improves auto body soundproofing.

**OUTSTANDING PROPERTIES:** A low cost product which requires no special tools or skills to apply. One can may be used for many different applications.

**USE DIRECTIONS:** Shake can until agitator ball moves freely. Surface to be sprayed should be clean and dry. Contents should be at room temperature. Hold can at 12 inches from surface to be sprayed. Apply a uniform coating. After use, clean nozzle by inverting can and spraying a short burst.

**PRODUCT LIMITATIONS:** Product is not intended to be a replacement for OEM or professional undercoating. This product is available in plain or rubberized versions. The rubberized version remains more flexible.

**PRECAUTIONS:** Contain a mixture of Asphalt, Attapulugus Clay/Talc, Styrene Butadien Rubber, Aromatic Petroleum Distillate (CAS# 1330-20-7), Aliphatic Petroleum Distillate (CAS# 8052-41-3) and Isobutane/Propane Propellant. Extremely flammable. Eye and skin irritant. Harmful or fatal if swallowed. Vapor harmful. **FIRST AID:** For eye contact, flush thoroughly with water for 15 minutes while lifting eyelids. Consult a physician if adverse effects persist. For skin contact, wash thoroughly with soap and water. Remove contaminated clothing and launder before re-use. If swallowed, DO NOT INDUCE VOMITING! DO NOT ADMINISTER ADRENALINE OR EPINEPHRINE! Get medical attention immediately! If inhaled, Move to fresh air immediately. If breathing is difficult, administer oxygen; if breathing has stopped, apply artificial respiration. Keep warm and summon medical assistance.

**STORAGE & HANDLING:** Store in a cool, dry, well ventilated area. Do not puncture or incinerate container. Do not expose to heat, sparks, open flames or temperatures above 120 F. Exposure to high temperatures may cause bursting. Do not place on radiator, stove or in direct sunlight. Keep from contact with electrical connections such as battery terminals. Do not spray on or close to exhaust systems or catalytic converters. Use with adequate ventilation. Avoid contact with skin or eyes. Wearing contact lenses while working with this product is inadvisable. Keep away from children.

**DISPOSAL:** Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

**CONTAINER DESCRIPTION:** Aerosol-16 weight ounce fill.

**SPECIAL NOTATIONS:** T16-17R (rubberized) is the more flexible of the two products.

## Radiator Specialty Company

P.O. BOX 34689 / CHARLOTTE, N.C. 28234 / TELEPHONE 704-377-6555

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.